Wright State University **CORE Scholar**

Special Session 5: Carbon and Oxide Based Nanostructured Materials (2012)

Special Session 5

6-1-2012

AC Magnetic Heating of Superparamagnetic Fe and Co Nanoparticles

Anna Lukawska

Zafrullah Jagoo

Gregory Kozlowski Wright State University - Main Campus, gregory.kozlowski@wright.edu

Zafer Turgut

Hiroyuki Kosai

See next page for additional authors

Follow this and additional works at: http://corescholar.libraries.wright.edu/ss5 2012



Part of the Physics Commons

Repository Citation

Lukawska, A., Jagoo, Z., Kozlowski, G., Turgut, Z., Kosai, H., Sheets, A., Bixel, T., Wheatley, A., Abdulkin, P., Knappett, B., Houlding, T., & Degirmenci, V. (2012). AC Magnetic Heating of Superparamagnetic Fe and Co Nanoparticles. . http://corescholar.libraries.wright.edu/ss5 2012/3

This Presentation is brought to you for free and open access by the Special Session 5 at CORE Scholar. It has been accepted for inclusion in Special Session 5: Carbon and Oxide Based Nanostructured Materials (2012) by an authorized administrator of CORE Scholar. For more information, please contact jane.wildermuth@wright.edu, riley.stoermer@wright.edu.

maintaining the data needed, and c including suggestions for reducing	lection of information is estimated to completing and reviewing the collect this burden, to Washington Headqu uld be aware that notwithstanding ar DMB control number.	ion of information. Send comments arters Services, Directorate for Infor	regarding this burden estimate mation Operations and Reports	or any other aspect of th , 1215 Jefferson Davis l	is collection of information, Highway, Suite 1204, Arlington			
1. REPORT DATE 01 JUN 2012	2. REPORT TYPE			3. DATES COVERED 00-00-2012 to 00-00-2012				
4. TITLE AND SUBTITLE				5a. CONTRACT NUMBER				
AC Magnetic Heat	anoparticles	5b. GRANT NUMBER						
				5c. PROGRAM ELEMENT NUMBER				
6. AUTHOR(S)				5d. PROJECT NUMBER				
				5e. TASK NUMBER				
				5f. WORK UNIT NUMBER				
	ZATION NAME(S) AND AC ersity,Physics Depar 5435	` '	enn	8. PERFORMING REPORT NUMB	GORGANIZATION ER			
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)				
					11. SPONSOR/MONITOR'S REPORT NUMBER(S)			
12. DISTRIBUTION/AVAIL Approved for publ	LABILITY STATEMENT ic release; distributi	ion unlimited						
13. SUPPLEMENTARY NO 8th International C Rights License	otes Conference on Diffus	sion in Solids and Li	quids, 2012,Govo	ernment or F	ederal Purpose			
14. ABSTRACT								
15. SUBJECT TERMS								
16. SECURITY CLASSIFIC	17. LIMITATION OF	18. NUMBER	19a. NAME OF					
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified	Same as Report (SAR)	OF PAGES 16	RESPONSIBLE PERSON			

Report Documentation Page

Form Approved OMB No. 0704-0188

Authors Anna Lukawska, Zafrullah Jagoo, Gregory Kozlowski, Zafer Turgut, Hiroyuki Kosai, Alexander Sheets, Tyler Bixel, Andrew Wheatley, Pavel Abdulkin, Benjamin Knappett, Thomas Houlding, and Volkan Degirmenci					



AC Magnetic Heating of Superparamagnetic Fe and Co Nanoparticles

Anna Lukawska, Zafrullah Jagoo, and Gregory Kozlowski

Wright State University, Physics Department 3640 Col. Glenn Hwy., Dayton, OH 45435, USA

Zafer Turgut, Hiroyuki Kosai, Alexander Sheets, and Tyler Bixel Propulsion Directorate, AFRL, Wright-Patterson AFB, Ohio 45433, USA

Andrew Wheatley, Pavel Abdulkin, and Benjamin Knappett

Cambridge University, Chemistry Department, Lensfield Road, Cambridge CB2 1EW, UK

Thomas Houlding, and Volkan Degirmenci

Queen's University Belfast, School of Chemistry & Chemical Engineering, Stranmillis Road, Belfast BT9 5AG, Northern Ireland, UK






Content

- Introduction
- Magnetism
- Superparamagnetism
- Heating mechanisms
- System
- Analysis tools
- Fe
- Co
- Summary



Magnetism





- Magnetic materials are classified by their susceptibility, x to magnetic fields:
 - Diamagnetic negative χ,
 - Paramagnetic small and positive χ,
 - Ferromagnetic large and positive χ.
 - In a large magnetic field the magnetic moments within the material align with the field, giving the saturation magnetization, $\mathbf{M_S}$. As the magnitude of the field decreases the total magnetization decreases and reaches at zero field the remanent magnetization, $\mathbf{M_R}$. The coercive field $\mathbf{H_C}$ must be applied to get back zero magnetization.
- Nanoparticles with diameter less than 100nm have a single magnetic domain, a uniaxial anisotropy (the magnetic energy is the lowest when particles' magnetization has the same orientation as an anisotropy axis)
- Difference between maximum and minimum magnetic energies (magnetization pointing along the anisotropy axis and perpendicular to it) is:

$$\Delta E = KV \sin^2 \theta$$

where **KV** is an energy barrier, **K** is the anisotropy constant, and **V** is volume.



Superparamagnetism

- KV value gets smaller as ferromagnetic nanoparticles (<100nm) gets smaller, and at some point it is comparable with the thermal energy k_BT.
- Assuming that particles are immobilized, this leads to a spontaneous random orientation of the magnetic moment inside the particles (zero remanence magnetization and coercivity, so no hysteresis).
- The magnetization will be zero until it will be biased in one direction by applied an external magnetic field. In this state the particle is superparamagnetic.
- The lifetime of particles magnetization (the time which the systems need to achieve zero magnetization after an external magnetic field is switched off), is given by Néel process $\tau_{N} = \tau_{0}e^{\left(\frac{KV}{k_{B}T}\right)}$



Heating Mechanism

- Disorder (high entropy) assembly of superparamagnetic nanoparticles (SN)
- Magnetized by magnetic field
- SN go to a highly ordered (low entropy) state
- Heat is added to the adiabatic system



Heating Mechanism (1)

• The first thermodynamic law gives:

$$dU = \delta W + \delta Q = HdB$$

where, U - the internal energy; W - the magnetic work done on the system, H [A/m] - the magnetic field intensity, B [T] - the induction; Q is the heat added to the system (δQ =0, adiabatic process).

- Heating is a thermodynamic mechanism that relies on the fact that in a high-frequency magnetic field the nanoparticles magnetization is always trying to catch up with the applied filed.
- Since H and B are collinear, only magnitudes are required:

B= μ_0 H+M, where μ_0 =4 π ·10⁻⁷ [Tm/A] is the permeability of free space. Thus, the change in the internal energy is:

$$\Delta U = \mu_0 \oint Hd(H+M) = -\mu_0 \oint MdH$$

 When the magnetization lags the field, the integrand is negative, indicating that magnetic work is converted to internal energy.



Heating Mechanism (2)

For ferrofluids the magnetization can be defined as a complex susceptibility: $\chi = \chi' - i\chi''$ Since, $\chi = \frac{\chi_0}{1+i\omega\tau}$ then $\chi'' = \frac{\omega\tau\chi_0}{1+(\omega\tau)^2}$

The magnetic field intensity is: $H(t) = H_0 cos\omega t = Re\{H_0 e^{i\omega t}\}$

With $dH = -H_0 \omega \sin \omega t$

The magnetization is:

 $M(t) = \chi H(t) = Re \big\{ \chi H_0 e^{i\omega t} \big\} = Re \big\{ (\chi' - i\chi'')(cos\omega t + isin\omega t) \big\} = H_0 \big(\chi' cos\omega t + \chi'' sin\omega t + \chi'' sin\omega t \big) + H_0 \big(\chi' cos\omega t + \chi'' sin\omega t + \chi'' sin\omega t \big) + H_0 \big(\chi' cos\omega t + \chi'' sin\omega t + \chi'' sin\omega t \big) + H_0 \big(\chi' cos\omega t + \chi'' sin\omega t + \chi'' sin\omega t \big) + H_0 \big(\chi' cos\omega t + \chi'' sin\omega t + \chi'' sin\omega t \big) + H_0 \big(\chi' cos\omega t + \chi'' sin\omega t + \chi'' sin\omega t \big) + H_0 \big(\chi' cos\omega t + \chi'' sin\omega t + \chi'' sin\omega t \big) + H_0 \big(\chi' cos\omega t + \chi'' sin\omega t + \chi'' sin$

Therefore, the change in internal energy is:

$$\Delta U = \mu_0 \omega H_0^2 \chi^{\prime\prime} \int\limits_0^{\frac{2\pi}{\omega}} sin^2 \omega t dt = \mu_0 \omega H_0^2 \chi^{\prime\prime} \frac{\pi}{\omega} = \mu_0 H_0^2 \chi^{\prime\prime} \pi$$


The volumetric power *P* generated by the assembly of nanoparticles and that heats surrounding environment is:

$$P = f\pi\mu_0 H_0^2 \chi'' \qquad P = f\pi\mu_0 H_0^2 \frac{\omega \tau \chi_0}{1 + (\omega \tau)^2} = f\pi\mu_0 H_0^2 \frac{2\pi f \tau \chi_0}{1 + (2\pi f \tau)^2}$$

where, τ is the effective relaxation time (due to Neel processes $\tau = \tau_N$).




System



- A custom-made power supply
- A 20-turn insulated copper coil in the shape of a spiral solenoid
- Cooling is done with water
- A fiber-optic temperature sensor with an accuracy of 0.0001 K
- At frequency 348 kHz the magnetic field with magnitude of 20.6 µT is generated inside the coil



Analysis tools



- SAR (Specific Absorption Rate) = SPL (Specific Power Loss) [W/g]
- Normalized SPL for different samples with different mass SPL'=SPL/m [W/g^2]



Co


- 5 different samples were measured
- Single-domain size limit: 15nm
- Superparamagnetic size limit: 6nm
- Heat capacity [J/°C g] = 0.4198

Nanoparticle	Diameter [nm]	Coating thickness [nm]	Coating	Coercivity [Oe]	SPL' [W/g^2]	Туре
Co31	6.5	~ 0.3-0.6	bis(2-ethylhexyl)sulfosuccinate	0	0.351	Superparamagnet
Co51	7.3	~1	Oleic acid+Dibutylamine	0	0.378	Superparamagnet
Co41	8.2	<2	Oleic acid +	0	1.316	Superparamagnet
			Triphenylphosphine			
Co1	8.7	~1	Oleic acid	≥0	0.176	Single-Domain
						Ferromagnet
Co21	20	~ 1.6	PVP	601	0.147	Multi-Domain
						Ferromagnet



Co

The maximum specific power loss or the highest heating rate for Co magnetic nanoparticles was achieved for particles of 8.2 nm in diameter coated with oleic acid to avoid its oxidation.





Fe

- 3 different samples were measured
- Single-domain size limit: ~15nm
- Superparamagnetic size limit: ~10nm
- Heat capacity [J/°C g] = 0.4504

Nanoparticle	Diameter [nm]	Coating thickness [nm]	Coating	Coercivity [Oe]	SPL' [W/g^2]	Туре
Fe7	5.6	~ 1nm	oleic acid	0	0.481	Superparamagnet
Fe6	11.3	~ 1nm	oleic acid	0	1.386	Superparamagnet
Fe5	20	~ 1nm	oleic acid	≥0	0.344	Multi-domain Ferromagnet



Summary

- Those are preliminary results and they demand further investigation.
- Observed that Co with 8.2 nm diameter and Fe with 11.3 nm diameter in magnetic field of 20.6 μT, (348kHz, 15A) gave the highest heating rates from investigated nanoparticles.
- One of next steps would be to immerse particles in fluid.

THANK YOU